



US009664331B1

(12) **United States Patent**
Caputa

(10) **Patent No.:** **US 9,664,331 B1**
(45) **Date of Patent:** **May 30, 2017**

- (54) **EXTENDABLE WINDOW PROP**
- (71) Applicant: **Carmelo Caputa**, St. Louis, MO (US)
- (72) Inventor: **Carmelo Caputa**, St. Louis, MO (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **15/240,795**
- (22) Filed: **Aug. 18, 2016**

4,763,865 A *	8/1988	Danner	F16M 11/38
				108/118
5,927,664 A *	7/1999	Schmidt	A47L 1/00
				248/176.1
5,979,854 A *	11/1999	Lundgren	E04F 21/1822
				248/354.3
6,075,440 A	6/2000	Carroll		
6,417,770 B1	7/2002	Sturznicke		
D485,742 S	1/2004	Heberle		
8,162,272 B2 *	4/2012	Trott	A47L 1/00
				248/176.3
8,469,427 B1 *	6/2013	Mejia	B66F 19/00
				294/209
9,599,278 B2 *	3/2017	Ruckman	A47L 3/00
2010/0096529 A1 *	4/2010	Kritsky	E06B 3/5063
				248/407

- (51) **Int. Cl.**
F16M 11/28 (2006.01)
E04G 25/04 (2006.01)
E04F 21/18 (2006.01)
A47L 1/00 (2006.01)
- (52) **U.S. Cl.**
CPC **F16M 11/28** (2013.01); **E04G 25/04** (2013.01); **A47L 1/00** (2013.01); **E04F 21/1805** (2013.01); **F16M 2200/028** (2013.01)
- (58) **Field of Classification Search**
CPC .. F16M 11/28; F16M 11/26; F16M 2200/028; A47L 1/00; E05Y 2800/744; E05Y 2800/692; E05Y 2900/148; F16B 7/10; E04G 25/1061; E04G 25/04
USPC ... 248/354.5, 158, 161, 188.1, 188.2, 188.5, 248/354.1
See application file for complete search history.

FOREIGN PATENT DOCUMENTS

EP	1282123	10/2008
WO	WO2006053276	5/2006

* cited by examiner

Primary Examiner — Anita M King

(57) **ABSTRACT**

An extendable window prop for supporting double-hung windows includes a pole that is of adjustable length. A crossbar is coupled to and extends perpendicularly from an upper end of the pole. A first rod is coupled proximate to the upper end of the pole and extends substantially perpendicularly from the pole. The first rod is substantially perpendicular to the crossbar. A second rod is coupled to and extends substantially perpendicularly from the first rod distal from the pole. The second rod is transverse to the pole. The crossbar is positioned on the pole such that the crossbar is configured to position a first window. The first window is supported by the pole. The second rod is positioned on the first rod such that the second rod is positioned to abut a frame of the first window that is positioned on the crossbar.

14 Claims, 4 Drawing Sheets

- (56) **References Cited**
U.S. PATENT DOCUMENTS
1,247,622 A 11/1917 Berrigan
2,358,865 A * 9/1944 McPherson E04F 21/1805
4,300,796 A 11/1981 Lane 248/188.7

